



SPECIFICATII TEHNICE

---

INVERTOR ONGRID  
**GROWATT**  
MIN 2500~6000 TL-XE

---

# MIN 2500~6000 TL-XE

- Maximum efficiency 98.4%
- Dual MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display



P O W E R  
- I N G O  
T O M O -  
R R O W O

powering tomorrow  
**Growatt**



Datasheet	MIN 2500TL-XE	MIN 3000TL-XE	MIN 3600TL-XE	MIN 4200TL-XE	MIN 4600TL-XE	MIN 5000TL-XE	MIN 6000TL-XE
<b>Input data (DC)</b>							
Max. recommended PV power (for module STC)	3500W	4200W	5040W	5880W	6440W	7000W	8100W
Max. DC voltage	500V	500V	550V	550V	550V	550V	550V
Start voltage	100V						
Nominal voltage	360V						
MPP voltage range	80V-500V	80V-500V	80V-550V	80V-550V	80V-550V	80V-550V	80V-550V
No. of MPP trackers	2						
No. of PV strings per MPP tracker	1						
Max. input current per MPP tracker	12.5A						
Max. short-circuit current per MPP tracker	16A						
<b>Output data (AC)</b>							
AC nominal power	2500W	3000W	600W	4200W	4600W	5000W	6000W
Max. AC apparent power	2500VA	3000VA	3600VA	4200VA	4600VA	5000VA	6000VA
Nominal AC voltage (range*)	230V (180-280V)						
AC grid frequency (range*)	50/60 Hz (45-55Hz/55-65 Hz)						
Max. output current	11.3A	13.6A	16A	19A	20.9A	22.7A	27.2A
Adjustable power factor	0.8leading...0.8lagging						
THDi	<3%						
AC grid connection type	Single phase						
<b>Efficiency</b>							
Max. efficiency	98.2%	98.2%	98.2%	98.4%	98.4%	98.4%	98.4%
European efficiency	97.1%	97.1%	97.2%	97.5%	97.5%	97.5%	97.5%
MPPT efficiency	99.9%						
<b>Protection devices</b>							
DC reverse polarity protection	yes						
DC switch	yes						
AC/DC surge protection	Type II / Type III						
Insulation resistance monitoring	yes						
AC short-circuit protection	yes						
Ground fault monitoring	yes						
Grid monitoring	yes						
Anti-islanding protection	yes						
Residual-current monitoring unit	yes						
AFCL protection	Optional						
<b>General data</b>							
Dimensions (W / H / D)	375/350/160mm						
Weight	10.8kg						
Operating temperature range	-25°C ... +60°C						
Noise emission (typical)	≤35 dB(A)						
Nighttime power consumption	< 1W						
Topology	Transformerless						
Cooling	Natural convection						
Protection degree	IP65						
Relative humidity	0-100%						
Altitude	4000m						
DC connection	H4/MC4(Optional)						
AC connection	Connector						
Display	OLED+LED/WIFI+APP						
Interfaces: RS485 / USB/WI-FI/ GPRS/ RF/LAN	Yes/Yes/Optional/Optional/Optional /Optional						
Warranty: 5 years / 10 years	Yes /Optional						

CE, CEI 0-21, VDE-AR-N 4105, VDE 0126-1-1, UTE C 15-712-1, EN 50549, IEC 62116, IEC 61727, G99, C10/C11, UNE217001, UNE206007, PO12.2

\* The AC voltage and frequency range may vary depending on specific country grid standard. All specifications are subject to change without notice.